

**Dimensions.**

width without selvedge : 140 piece length : 50

Composition.

% in totaal fabric : 100%PES
% in warp : 100%PES
% in weft : 100%PES
% in pile : 100%PES
% in ground : 100%PES
weight per rm : 430g/rm weight per sqm : 307 g/sqm

Densities.

pile : 0 yarns/cm
warp : 15 yarns/cm
weft : 28 picks/cm

Tests.

Tensile strength EN ISO 13934-1
warp : 800N
weft : 689N
Tear strength EN ISO 13937-3
warp : 112N
weft : 178N
Seam slippage EN ISO 13936-2 (180 N)
warp : 1,2mm
weft : 1mm
Abrasion resistance EN ISO 12947-2
cycles : 100000cycles
Pilling EN ISO 13945-2
after 2000 cycles : 4

Colour fastness.

Colour fastness to light (DIN 54004 - DIN 61010T1-3/94 requires for light 3 - middle 4 - dark 5)
light colours : 4 middle colours : 4 dark colours : 5
Colour fastness to rubbing (DIN 54021 - DIN 61010T1-3/94 requires dry 4 - wet 3)
dry : 4 wet : 3

Fire safety regulations.

BS5852 p.1 Not tested yet
ISO EN1021-1 AND -2 Not tested yet
BS 5852 p.2 CRIB 5 Not tested yet
BS 5867 B (curtains) Not tested yet
BS 7176 Medium Hazard Not tested yet
NF P92-504(M1) Not tested yet
IMO A652 Not tested yet
NFPA 701 Not tested yet

Special finishing.

Model: 8267 Pashmira

Presentation: PIECE DYED

Type of fabrics: KNITTED

Yarn:
Warp: CONTINUE FILAMENT
Weft: CONTINUE FILAMENT
Pile: CONTINUE FILAMENT
Base: CON

Texturized: 0

Finish: DYED

Construction: MACHE

Weight: 430 g/m running m

Custom code: 60019200

Yarns:
SE SILK
CO COTTON
LI FLAX
CA ACETATE
CMD MODAL
CV VISCOSE
PAN ACRYLIC
MAC MODACRYLIC
PA POLYAMIDE
PES POLYESTER
PP POLYPROPYLENE
WO WOOL
MTF METALLISED

CARE INSTRUCTIONS

Care instructions

1. Professional dry-cleaning
2. Protect the fabric from direct sunlight. We recommend vacuum on regular basis using low suction and rotation on reversible cushions. Treat spills and stains as soon as possible. Gently scrape any soil or mop any liquid from the surface of the fabric and do not scrub. Apply appropriate cleaning agents strictly according to instructions to remove the residue of the spill. It is difficult to give instructions on doing this yourself due to the variety of different fibre and fabric constructions, each of which require specialist cleaning techniques. Seek professional advice. Do not saturate the fabric with water or other cleaning agents. The methods for cleaning should be applied to all areas of the furnishing and not to isolated parts.

Colour matching

3. Whilst every effort is made to ensure that colours correspond closely to those illustrated in our sample book, we can not guarantee to match samples exactly.

Available finishes

4. back-lick, standard finish, fire retardant to BS 5852, treated with a soil repellent product, back-lick + treated with a soil repellent product, fire retardant to BS5852 + treated with a soil repellent product.

Remarks

5. This is a pile fabric and will flatten as a characteristic. Regular light vacuuming or brushing, with a soft brush is necessary for optimal appearance retention.
6. This fabric, due to its type of construction, can be snagged easily. Care must be taken to avoid sharp edged toys, buckles, jewellery, domestic pets or vacuum cleaner fittings damaging the threads of the fabric in this way. If snags do occur, carefully push them back into the fabric with a fine but blunt tool. Under no circumstances attempt to pull them. Flatweave covers do have a tendency to "pill" in the early months of use but this will decrease with time

Soil Resistant Finishes : Where your furniture has been treated with a protective finish by a third party, we as manufactures cannot accept any liability for problems caused by such treatment or arising from it, of any kind. Nor can we accept liability for the re-treatment of any replacement parts which may be supplied at any time.

Maintenance.

