


Tuscon 8445

GENERAL INFORMATION

Composition	100% PES
Weight g/m ²	425g
Weight g/Lm	629g
Width	148cm
Min. usable Width	138cm
Piece Length	35m
Tariff code	58013600

CLEANING INSTRUCTIONS



TECHNICAL DATE

• SHRINKAGE	40° WARP	-0.20%
	WEFT	-0.22%
• MARTINDALE ABRASION ISO12947-2 1998	END POINT	>100 000
	CHANGE IN COLOR	5
• SEAM SLIPPAGE EN ISO 13936-2	WARP	4mm
	WEFT	4mm
• TEAR STRENGTH EN ISO 13937-3:2000	WARP	116N
	WEFT	34N
• TENSILE STRENGTH ISO 13934-1	WARP	1600N
	WEFT	750N
• COLOUR FASTNESS FOR RUBBING EN ISO 105-X12	WARP DRY	4/5
	WARP WET	4
	WEFT DRY	4/5
	WEFT WET	4
• COLOUR FASTNESS TO LIGHT EN ISO 105-B02	GRADE	100: 5
	GRADE	104: 5/6
	GRADE	107: 6
	GRADE	200: 6
	GRADE	202: 6+
	GRADE	204: 5
	GRADE	300: 5
	GRADE	301: 5
	GRADE	303: 5
	GRADE	400: 5
	GRADE	401: 5
	GRADE	402: 4/5
	GRADE	500: 4/5
	GRADE	503: 4/5
	GRADE	506: 5
	GRADE	601: 5



Tuscon 8445

GRADE	604: 4/5
GRADE	605: 4/5
GRADE	608: 4/5
GRADE	609: 4/5
GRADE	610: 4/5
GRADE	700: 4/5
GRADE	702: 5
GRADE	703: 4/5
GRADE	705: 5
GRADE	800: 4
GRADE	801: 3/4
GRADE	804: 5
GRADE	805: 4/5
GRADE	806: 4
GRADE	807: 4
GRADE	900: 4
GRADE	902: 4
GRADE	904: 5
GRADE	906: 4

• PILLING ON MARTINDALE	500	5
ISO 945-2:2000	1000 RUBS	5
	2000 RUBS	5
	5000 RUBS	4/5